




Fitting for top-running glass doors up to 100 kg (220 lbs.), with surface mounted running track or running track flush with the ceiling. Optionally with soft and self closing mechanism. Ceiling mounting. Minimal installation height. Wall pocket solution.

Product-Highlights	 Comfort	Accessible opening and soft and self closing at both sides from door widths of 800 mm (2' 7 1/2")
	 Productivity	Door can be installed in pocket after construction is complete
	 Reliability	Performance guarantee: 15 years for private use and 7 years for commercial use on incomparably low opening forces of max. 22 N

Technical guidelines	Max. Door weight	100 kg (220 lbs.)
	Door thickness	8–12.7 mm (5/16" to 1/2")
	Max. Door height	4000 mm (13' 1 15/32")
	Max. Door width	1500 mm (4' 11 1/16")
	Max. Opening width	1465 mm (4' 9 11/16")
	Height adjustable	+/- 3 mm (1/8")
	Soft close	Yes
	Guaranteed opening force with damping*	Max. 22 N (fully accessible)
	Door material	Glass
	Finish color of visible profiles	Aluminum anodized / aluminum stainless steel effect

System options	Ceiling mounting	Yes
	Ceiling mounting recessed	Yes
	Top-running	Yes

Application area	Utilization light / semi-public access	Yes
	Utilization medium / semi-public access	Yes
	Utilization high / public access	Yes

Tests Building hardware – Hardware for sliding doors and folding doors according to EN 1527 / 2013
 – Duration of functionality: Class 6 (highest class = 100,000 cycles)

*see warranty

Warranty

Performance guarantee for all official Hawa Junior 100 versions with magnetic soft close system: Guaranteed opening force of the sliding doors of max. 22 N for 15 years in domestic use and 7 years in commercial use

The performance guarantee is valid worldwide with the exception of contractual partners with their registered office/residence in the USA and use of the products by end users with registered office/residence in the USA.

Additional function guarantee on all parts other than those subject to wear and tear: 2 years

Product Design

Hawa Junior 100 GP Pocket consisting of running track (aluminum wall thickness 2.9 mm (1/8")), running gear with friction bearing rollers, stopper, spring buffer or soft closing mechanism Hawa SoftMove 100, Glass suspension with point fixing, bottom guide with zero clearance

Optional:

(...) Set for installable and removable running track, aluminum

Interfaces

Door leaf

- Glass processing for glass holders
- Positive-fit glass fixing with point fixing

Assembly set

- The retainer profile is installed during the creation of the pocket construction

Pocket construction

- Pocket construction must be taken care of by the customer